

# PRODUCT INFORMATION



Lubricants - Engine Oil - Motorcycle Motor Oils

Version: 306/10a

## SynPower™ 4T SAE 10W-40

Premium quality synthetic motor oil for four-stroke motorcycle engines. Formulated for ultimate performance under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers.

### Approvals & Specifications

API SN
JASO MA
JASO MA2

### Applications

Four-stroke motorcycle engines where SAE 10W-40 motor oil is recommended.

Wet clutch compatible and recommended for Japanese and other motorcycles where API SN or JASO MA fluids are specified.

Can be used in high-powered motorcycles.

Optimized for lubrication systems where engine, gearbox and clutch are integrated (wet sump).

Can be used for motorcycles running in cold weather conditions.

### Features & Benefits

#### Ultimate protection & performance

SynPower 4T engine oil is formulated with the highest quality base oils and latest additives to ensure ultimate protection and performance under all operating conditions. Designed to fulfill the latest standards of leading motorcycle engine manufacturers.

#### Wear protection

Provides ultimate protection against wear under all operating conditions. Designed to protect high performance engines.

#### Engine cleanliness

Keeps engine extremely clean by minimizing deposits.

#### Wet clutch compatible

Optimal frictional characteristics for maximum power transfer, smooth shifting and proper protection of the wet clutch. (JASO MA2 approved).

#### Easy starts

Recommended for quick starting, even under very cold conditions or after long periods of engine inactivity.

# PRODUCT INFORMATION



## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit <https://www.valvolineglobal.com/en-eur/> or <http://pisheets.valvolineglobal.com>

## Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

SynPower 4T	
<b>SAE Viscosity Grade</b>	10W-40
<b>Viscosity, mm<sup>2</sup>/s @ 100°C</b> ASTM D-445	14.5
<b>Viscosity, mm<sup>2</sup>/s @ 40°C</b> ASTM D-445	94.2
<b>Viscosity Index</b> ASTM D-2270	160
<b>TBN, mg KOH/g</b> ASTM D-2896	7.6
<b>Pour Point, °C</b> ASTM D-5949	-36
<b>Specific Gravity @ 15.6°C</b> ASTM D-4052	0.855
<b>Flash Point, COC, °C</b> ASTM D-92	217

**This information only applies to products manufactured in the following location(s):  
Europe**

™ Trademark, Valvoline Global Operations ©2024 Valvoline Global Operations

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

## Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvolineglobal.com>

## Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

## Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 306/09a