

PRODUCT INFORMATION



Lubricants - Engine Oil - Passenger Car Motor Oils

Version: 038/16

Valvoline™ SynPower™ FE 5W-30

VALVOLINE SynPower – OEM Approved Premium Grade Synthetic Motor Oil.

Formulated for ultimate performance and protection under all operating conditions, SynPower is designed to fulfil the latest standards of leading engine manufacturers.

Approvals & Specifications

Jaguar LandRover STJLR 03.5003

ACEA A5/B5

ACEA A7/B7

API SP

Renault RN0700

Suitable for use where Ford WSS-M2C913-A, B, C, D are specified

Ford diesel engines (Except Ford Ka TDCi 2009 > and Galaxy 1.9 TDi 2000-2006).

Applications

SynPower FE 5W-30 has been formulated to meet Jaguar Land Rover STJLR 03.5003 lubricant specification. FE 5W-30 is designed to maintain engine performance in vehicles, where a 5W-30 is recommended.

Specially formulated for use in passenger cars and light commercial vehicles with gasoline, diesel, and LPG engines.

For passenger cars and light commercial vehicles that require engine oil with the worldwide specifications, ACEA A7/B7 or ACEA A5/B5.

Suitable for engines running on mixtures of diesel and biofuel (MB Bio Oxidation Test).

Always check the owner's manual for the correct oil specification to use.

Features & Benefits

Protects Engine and Emissions System

SynPower engine oil is formulated with the highest quality base oils and latest additives to ensure ultimate protection and performance under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers.

Bio fuel compatibility

Designed for engines running on bio fuel mixtures (for example E85).

Engine cleanliness

Keeps engine extremely clean by minimizing deposits.

Fuel Economy

Low viscosity and special additives result in maximum reduction of friction which results in a lower fuel consumption.

Wear protection

Provides ultimate protection against wear under all operating conditions.

Excellent cold start performance

Instant oil flow at low temperatures provides easy cold starts and optimal lubrication within seconds after ignition.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit

www.valvolineeurope.com

For all OEM specifications visit:

<https://pisheets.valvoline.com/>

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

SynPower FE	
SAE Viscosity Grade	5W-30
Viscosity, mm ² /s @ 100 °C. ASTM D-445	9.7
Viscosity, mm ² /s @ 40 °C. ASTM D-445	54
Viscosity Index ASTM D-2270	170
Viscosity, mPa.s -30°C. ASTM D-5293	3555
TBN, mg KOH/g ASTM D-2896	12.4
Pour Point, °C ASTM D-5949	-45
Specific Gravity @ 15.6°C. ASTM D-4052	0.849
Flash Point, COC, °C. ASTM D-92	218

**This information only applies to products manufactured in the following location(s):
Europe**

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet

<http://sds.valvoline.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend storing all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 038/15

™ Trademark of Valvoline, registered in various countries © 2022

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.