

PRODUCT INFORMATION



Lubricants - Engine Oil - Passenger Car Motor Oils

Version: 095/03

Valvoline™ SynPower™ MST FE C6 0W-20

VALVOLINE SynPower – OEM Approved Premium Grade Synthetic Motor Oil.

Formulated for ultimate performance and protection under all operating conditions, SynPower is designed to fulfil the latest standards of leading engine manufacturers.

Approvals & Specifications

Dexos D (DD25BADB103)
Ford WSS-M2C952-A1
Jaguar Land Rover STJLR 03.5006
MB-Approval 229.71
Opel/Vauxhall OV 040 1547-A20
ACEA C6, C5
API SP, SN PLUS
ILSAC GF-6A
Recommended for use where Fiat 9.55535-DM1 is specified

Applications

SynPower MST FE C6 0W-20 has been formulated to meet Ford WSS-M2C952-A1 lubricant specification. MST FE C6 is designed to maintain fuel efficiency in light duty vehicles with advanced aftertreatment systems such as DPF's, GPF's and SCR, where a 0W-20 is recommended. Also suitable for other vehicles where a 0W-20 ACEA C6 or C5 engine oil may be used.

Always check the owner's manual for the correct oil specification to use.

Features & Benefits

Ultimate protection and performance

SynPower engine oil is formulated with the highest quality base oils and latest additives to ensure ultimate protection and performance under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers.

Engine cleanliness

Keeps engine extremely clean by minimizing deposits.

Fuel Efficiency (FE)

Low viscosity and special additives result in maximum reduction of friction which results in a lower fuel consumption.

Wear protection

Provides ultimate protection against wear under all operating conditions.

Excellent cold start performance

Instant oil flow at low temperatures provides easy cold starts and optimal lubrication within seconds after ignition.

Mid SAPS Technology (MST)

Valvoline's MST additive system is formulated to provide the highest level of engine protection whilst not adversely impacting the performance of emissions control technologies such as Diesel Particulate Filters (DPF), Gasoline Particulate Filters (GPF) and Selective Catalytic Reduction (SCR) systems. Formulated with advanced detergent and anti-wear components the MST additive system minimizes filter blocking, catalyst deactivation and sulphate particulate creation; helping to maintain the efficient operation of the vehicle.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit

www.valvolineeurope.com

For all OEM specifications visit:

<https://pisheets.valvoline.com/>

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

SynPower MST FE C6 Motor Oil	
SAE Viscosity Grade	0W-20
Viscosity, mm ² /s @ 100 °C. ASTM D-445	8,3
Viscosity, mm ² /s @ 40 °C. ASTM D-445	41
Viscosity Index ASTM D-2270	186
Viscosity, mPa.s -35°C. ASTM D-5293	<6200
TBN, mg KOH/g ASTM D-2896	9,5
Pour Point, °C ASTM D-5949	-42
Specific Gravity @ 15.6°C. ASTM D-4052	0,843
Flash Point, COC, °C. ASTM D-92	226

**This information only applies to products manufactured in the following location(s):
Europe**

™ Trademark of Valvoline, registered in various countries © 2023

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet

<http://sds.valvoline.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend storing all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 095/02